



INTERNATIONAL JOURNAL OF  
RESEARCH IN COMPUTER  
APPLICATIONS AND ROBOTICS

ISSN 2320-7345

**A REFLEXIVE WIRELESS CLAMMINESS  
SILL SCRUTINIZE FEELER BELIEF  
PEDESTAL ON DELIQUESCENT SALINE  
AND A WORDINESS PEDESTAL  
IRREPARABLE UTTER AMEND**

<sup>1</sup>C. Bala Saravanan, <sup>2</sup>A. Sri Janani, <sup>3</sup>G. Iniya

<sup>1</sup>Research Scholar, Vel Tech Multi Tech Dr. Rangarajan Dr.Saguunthala Engineering College Vel Tech Rangarajan Dr.Saguunthala R & D Institute of Science & Technology, Avadi, Chennai, Tamil Nadu, **India**.


<sup>2,3</sup> Vel Tech Multi Tech Dr.Rangarajan Dr.Sakunthala Engineering College, Avadi, Chennai, Tamil Nadu, **India**.  
E-Mail: - <sup>1</sup>cvbsin@gmail.com, <sup>2</sup>srijanu30@gmail.com, <sup>3</sup>iniya.ravi0409@gmail.com

**Abstract:** - Reflexive RFID transponder application which requires incorporated feelers can to a enormous extent gain on or after avant-garde sense strategy more than ever in circumstances where there is a could do with to continuously keep an eye on ecological belongings without have right of entry to an incorporated spring of electric get-up-and-go or an omnipresent reader reorganization within drop a line to range. in view of the fact that, in an hodgepodge of cases, in sequence about the violation of a threshold value is of interest, unusual sense strategies exploiting irremediable phenomena not considered or even avoided before, have the potential to find successful use in low-cost (e.g. chip-based sensor RFIDs) or buck cost wireless feeler appliance. In this cram, a stand-alone, simple, passive, wireless humidity threshold sensor concept and its realization are to be had. This exploits the deliquescence phenomenon of salts. Based on a double planar coil arrangement, for which a thrilling model is prearranged and a transfer role has been deduced, an oscillating trip is bent.

**Keywords** - Deliquescence, efflorescence, damp, inductively coupled resonant, irreversible, passive, saline, feeler, solitary exploit, state amend, and sill, wireless.

## 1. Introduction


Chip less RFID tags have the impending of feat mechanized costs akin to those of classic barcode labels a aspiration stretched promise nevertheless not yet accomplish by conventional chip-based RFID tags. Besides given that unique identification in order, a logical consequence is the integration of sensing Functionality, a enlargement trend previously pragmatic in established chip-based RFID applications [2], [3] and therefore also of significance in imminent transistor less RFID applications [4]. Hereby, a strong spur is to provide in sequence on the subject of whether a quantity of goods have been exposed to critical environmental conditions or not. This has necessitate offs the porch disobedience scrutinize of ecological contemplations performing art on the product, in the superlative case unremittingly for the occasion of its intact life phase.



**Figure 1:** Anticipated Wireless Feeler Concept

## 2. Deliquescence and Efflorescence of Saline


The majority of the inorganic equipment and several organic ones show deliquescent behavior. Sorbet water mist from the surrounding air causes a change from the rock-hard phase to the liquid phase. The phase transition, in which crystalline substances dissolve and an aqueous way out is fashioned is allied to a well-defined ambient relative humidity value, the deliquescence virtual damp (DVD). This value can be understood as a threshold below which it is thermodynamically sympathetic for a precious stone to stay solid and surrounded by water vapor, and above which it is thermodynamically favorable to outward facade an aqueous solution. in general it is unspoken that beneath the DVD, adsorbed water cannot cause the entire dissolution of the solid crystal while condensed liquid water can. Efflorescence is the opposing transition of the aqueous salt explanation from which a solid worthless stone organization is twisted due to hose down evaporation.



**Figure 2:** Preliminary State of The Spongy Absorber Media With No Saline Deposit In The External Sensor Expanse

## 3. Feeler Impression


Inductively tied, booming (ITB) feelers are effortless to assemble and to amalgamate, tolerate for unreceptive, short expanse, wireless wisdom. In order to determine effective electric permittivity make over in a depth dimensions, the twofold planar coil sensor pact in Fig.3 is wished-for. In contrast to solutions based on not tongue inductors and capacitors, the intrinsic intertwining capacitances of two connected spiral coils surrounding a measurement dimensions are misrepresented; [5] due to an eternal adjust in the dealings effectual thrilling permittivity. The coils, which are allied with a single wire, are placed below and above a porous absorber media.



**Figure 3:** Ultimate Shape of the Permeable Absorber Middling With Saline Dump In The Outer Feeler Constituency

#### 4. Dimension Intricate


Sketch elsewhere were voted for out in clammy and kindness illegal profundity board room (HC0020, Heraeus/V'otsch) which allows for a relative humidity variation between 34.95% at a temperature range of 25..90\_C as shown in Fig.4. An additional temperature and humidity [7] reference sensor (SHT15, Sensation), as part of a wireless sensor node (HUMITEMP, PRODAT), was placed in close proximity to the ICR sensor. The sensor reverberation occurrence and its change due to humidity influence, was monitored with a detection coil connected to a network analyzer (8753D, HP/Agilent). The S11-parameter of a 1-port reflection width was evaluated in the feeler effective occurrence vary.



**Figure 4:** similarity of a precise regularity rejoinder of an allusion thrilling activist bargain

#### 5. Tentative Consequences

The aim of the tentative inquiry is to craft obvious the likelihood of the wished for feeler opinion. The entire of the near be had investigational consequences were unhurried wirelessly based on the formerly described tentative setup with scrutinize sensors inductively tied to a detection coil. A typical sensor response due to the influence of humidity is shown in Fig.5. To embark on with the sensor tone occurrence phase in its prime state. If the deliquescence moisture is exceeded and the salt elucidation is bent, the feeler enters its fruition installment.



**Figure 5:** The Depth Setup Used to Study the Feeler Rejoinder under the Influence of Humidity Is Based On a Climate Chamber

## 6. Conclusion

In this work an irrevocable, wireless, rigid sensor cryptogram pedestal on the deliquescence deeds of brackish and their immutable allotment in a porous absorber media has been handy. This concept can be used to detect whether doorway clamminess impact has been outshine or not. The feeler hereby fulfills its scrutinize task not including the necessitate of a throw in of electric oomph and the in status of an entrance contravention is contained in the vigor value range. Shows potential tentative fallout of the feeler rejoinder in faith on special wetness ordeal phase have been offered. So far only conduct experimentation underneath laboratory circumstances were voted for out and no statistics commencing countryside exploration is vacant. Relevance needy ecological spring of pollution might be near, and could sway the sensor rejoinder.

## REFERENCES

- [1] S. Sauer and W.-J. Fischer, "Passive wireless irreversible humidity threshold sensor exploiting the deliquescence behavior of salts," in IEEE Sensors Conference Proceedings, 2012, pp. 1–4.
- [2] J. Heidrich, D. Brenk, J. Essel, G. Fischer, and R. Weigel, "The roots, rules, and rise of rfid," IEEE Microwave Theory and Techniques Society, vol. 11, pp. 78–86, 2010.
- [3] S. Sauer, U. Marschner, H. Gr'atz, and W.-J. Fischer, "Medical wireless vibration measurement system for hip prosthesis loosening detection," Sensordevices, International Conference on Sensor Device Technologies and Applications, vol. 3, pp. 9–13, 2012.
- [4] S. Preradovic and N. C. Karmakar, "Design of fully printable planar chipless rfid transponder with 35-bit data capacity," in Proceedings of the 39th European Microwave Conference, 2009, pp. 13–16.
- [5] B. Todd, M. Phillips, S. M. Schultz, A. R. Hawkins, and B. D. Jensen, "Low-cost rfid threshold shock sensors," IEEE SENSORS JOURNAL, vol. 9, pp. 464–469, 2009.
- [6] R. Fenner and E. Zdankiewicz, "Micromachined water vapor sensors: A review of sensing technologies," IEEE Sensors Journal, vol. 1, pp. 309–317, 2001.
- [7] Z. M. Rittersma, "Recent achievements in miniaturised humidity sensors - a review of transduction techniques," Sensors and Actuators A, vol. 96, pp. 196–210, 2002.

### Author Biography



C.BALA SARAVANAN received the M.Tech (I.T) from Sathyabama University in 2011, He stayed in orbit technologies as software engineer to develop health care automation tool. He is currently doing Ph.D in VELTECH Dr.RR & Dr.SR Technical University and working as an Assistant Professor in VelTech MultiTech Dr.R & Dr.SR Engineering College and IBM TGMC Project Coordinator. His research area is Data mining through Drug analysis.